

NL914C™ Night Vision Monocular

Features:

- Lightweight
- Extended Battery Life
- Push Button Design
- Automatic Brightness Control
- Variable Gain
- IR Illuminator
- 3X and 5X afocal objectives available
- Single AA Battery or CR123 battery
- Made in USA
- 2 Year Warranty



The NL914C™ Night Vision Monocular offers the user the performance and versatility of the AN/PVS-14 with an improved design. The NL914C™ has extended battery life offering the user up to 75 hours on one battery. The redesigned system includes push button design and is extremely lightweight (275g with battery). The NL914C™ is a very versatile night vision system offering hand-held, head/helmet mounted, and weapon mounted capability. The system features variable gain, built in IR-Illuminator and automatic brightness control (ABC).

Standard Accessories: Hard sided or soft carrying case, manual, eyecup, lens cover, demist shield, sacrificial window, weapon mount, head/helmet mount adapter, head mount assembly. The NL914C™ will also work with any optional PVS-14 accessories including, helmet mounts, 3x/5x afocal lenses, and advanced weapon mounts.

NIGHTLINE, INC.



www.Nightline.us
info@nightline.us

300 Industrial Drive
 Mountain City, TN 37683
 423-727-5900

Southern Tier Sales
 P.O. Box 16-0819
 Miami, FL 33186
 305-598-5357

Export of Night Vision devices is strictly prohibited without a valid export license issued by the US Department of State, Office of Defense Trade Controls, prescribed in the International Traffic in Arms Regulation (ITAR), Title 22, Code of Federal Regulations, Parts 120-130



Scan for more information

Technical Specifications

Technical Specifications		
Optics	Magnification	1X
	Field of View	40°
	Minimum focus range	25cm (9.8")
	Focal Length	25mm (.98")
	Diopter Adjustment	+2 to -6
	Eye Relief	25mm (0.98")
Mechanical	Controls	Push button design
	Variable Gain	±10 to >3,000
	Power Source	One 1.5 V AA battery or 1 CR123 battery
	Operation Time	up to 75 hours
	Weight (with battery)	275g
	Submersibility	20m (66')
	Operating Temperature	-51° to +50° C (-60° to +122° F)
Storage Temperature	-51° to +85° C (-60° to +185° F)	