

NL949B™ Aviator Goggles

Features:

- 40° Field of View
- Class A, Class B and Class C filters available
- Nightline, Inc. is an FAA Certified Repair Station for Aviator's Goggles
- Made in USA
- 2 Year Warranty



The NL949B™ is based on the US Military model AN/AVS-9 Aviator's Goggles. Improved situational awareness, system performance, in addition to ergonomic and technological enhancements benefit both military and civil operators.

The NL949B™ features binocular viewing for optimized depth perception. The large 25mm eyepieces provide improved eye relief enabling excellent viewing while easily accommodating eye glasses. Ergonomically designed interface controls including inter-pupillary adjustments and vertical, fore-aft, and tilt adjustments provide improved viewing of the entire system field of view (40 degrees). The objectives are filtered for operation with compatible aircraft lighting. Optional filters are available (Class A, Class B, and Class C).

Available accessories include: objective lens cover, Class A, B, or C objective lens, batteries, neck cord, Operator's Manual, soft carrying case, low-profile battery pack, COPS (Clip-On Power Supply), and lens paper. Optional counter weights for battery packs and daylight training are available.

NIGHTLINE, INC.



www.Nightline.us
info@nightline.us

300 Industrial Drive
 Mountain City, TN 37683
 423-727-5900

Southern Tier Sales
 13501 SW 128th, Unit 217
 Miami, FL 33186
 305-598-5357

Export of Night Vision devices is strictly prohibited without a valid export license issued by the US Department of State, Office of Defense Trade Controls, prescribed in the International Traffic in Arms Regulation (ITAR), Title 22, Code of Federal Regulations, Parts 120-130



Scan for more information

Technical Specifications

Optics	Magnification	1X
	Field of View	40°
	Focus Range	41cm (16") to ∞
	Focal Length	27mm (1")
	Diopter Adjustment	+2 to -6
	Eye Relief	25mm (1")
	Interpupillary adjustment	51 to 72 mm (2" to 2.8")
Mechanical	Vertical adjustment	25mm (1")
	Fore/Aft Adjustment	27mm (1.06")
	Tilt Adjustment	10° minimum
	Objective Adjustment	3/4 turn (338°)
	Automatic Breakaway	11 to 15g
	Power Source - Low Profile Battery Pack Clip On Power Supply	4AA batteries 2AA batteries
	Weight without battery	534g (20.8 oz)
	Submersibility	1m (3') for 30 minutes
Operating Temperature	-32° to +52° C (-25.6° to +125.6° F)	
Storage Temperature	-35° to +85° C (-31° to +185° F)	